

Specifications

SAMSUNG

| Model | | QB43C | QB50C | QB55C | QB65C | QB75C | QB85C | |
|----------------------------|-----------------------|--|---|---|---|---|---|---|
| Display Panel | Diagonal Size | 43 | 50 | 55 | 65 | 75 | 85 | |
| | Class | 42.5 | 48.5 | 54.6 | 64.5 | 74.5 | 84.5 | |
| | Measured | | | | | | | |
| | Resolution | 3,840 x 2,160 (16:9) | 3,840 x 2,160 (16:9) | 3,840 x 2,160 (16:9) | 3,840 x 2,160 (16:9) | 3,840 x 2,160 (16:9) | 3,840 x 2,160 (16:9) | |
| | Brightness (Typ.) | 350 nit | 350 nit | 350 nit | 350 nit | 350 nit | 350 nit | |
| | Orientation | Landscape/Portrait | Landscape/Portrait | Landscape/Portrait | Landscape/Portrait | Landscape/Portrait | Landscape/Portrait | |
| | Haze | 2% | 3% | 2% | 2% | 5% | 5% | |
| | Contrast Ratio (Typ.) | 4,000:1 | 4,000:1 | 4,000:1 | 4,000:1 | 4,000:1 | 4,000:1 | |
| | Type | VA | VA | VA | VA | VA | VA | |
| | Active Display Area | 941.184 (H) x 529.416 (V) | 1,095.84 (H) x 616.41 (V) | 1,209.6 (H) x 680.4 (V) | 1,428.48 (H) x 803.52 (V) | 1,650.24 (H) x 928.26 (V) | 1,872.0 (H) x 1053.01 (V) | |
| Pixel Pitch (mm) | 0.245 x 0.245 | 0.285 x 0.285 | 0.315 x 0.315 | 0.372 x 0.372 | 0.429 x 0.429 | 0.487 x 0.487 | | |
| Color Gamut | NTSC 72% | NTSC 72% | NTSC 72% | NTSC 72% | NTSC 72% | NTSC 72% | | |
| Operation Hour | 16/7 | 16/7 | 16/7 | 16/7 | 16/7 | 16/7 | | |
| Connectivity / Sound | Input | Video | HDMI 2.0 (3) | HDMI 2.0 (3) | HDMI 2.0 (3) | HDMI 2.0 (3) | HDMI 2.0 (3) | |
| | | Audio | N/A | N/A | N/A | N/A | N/A | N/A |
| | | USB | USB 2.0 x 2 | USB 2.0 x 2 | USB 2.0 x 2 | USB 2.0 x 2 | USB 2.0 x 2 | USB 2.0 x 2 |
| | Output | Video | N/A | N/A | N/A | N/A | N/A | N/A |
| | | Audio | Stereo mini Jack | Stereo mini Jack | Stereo mini Jack | Stereo mini Jack | Stereo mini Jack | Stereo mini Jack |
| | | USB | N/A | N/A | N/A | N/A | N/A | N/A |
| | WiFi / BT | O/O | O/O | O/O | O/O | O/O | O / O | |
| | External Control | RS232C (In/Out), RJ45 | RS232C (In/Out), RJ45 | RS232C (In/Out), RJ45 | RS232C (In/Out), RJ45 | RS232C (In/Out), RJ45 | RS232C (In/Out), RJ45 | |
| Speaker | 10W 2ch | 10W 2ch | 10W 2ch | 10W 2ch | 10W 2ch | 10W 2ch | | |
| Mechanical Spec | Dimension (mm) | Set | 969.5 x 557.8 x 28.5 | 1,124.1 x 644.8 x 28.5 | 1,237.9 x 708.8 x 28.5 | 1,456.8 x 831.9 x 28.5 | 1,682.3 x 960.4 x 28.5 | 1,904.3 x 1,085.3 x 28.5 |
| | | Package | TBD | TBD | TBD | TBD | TBD | TBD |
| | Weight (kg) | Set | 1,093 x 667 x 126 | 1,246 x 761 x 131 | 1,403 x 835 x 148 | TBD | TBD | TBD |
| | | Package | TBD | TBD | TBD | TBD | TBD | TBD |
| | VESA Mount | 200 x 200 | 200 x 200 | 200 x 200 | 400 x 300 | 400 x 400 | 400 x 400 | |
| VESA Mount Screw (Min-Max) | M8, 12~14mm | M8, 12~14mm | M8, 12~14mm | M8, 12~14mm | M8, 12~14mm | M8, 12~14mm | | |
| Bezel Width (mm) | 11.5 (Even) | 11.5 (Even) | 11.5 (Even) | 13.4 (Even) | 13.4 (Even) | 13.9 (Even) | | |
| Features | Key | UHD Signage with Built-in MagicInfoS10, SSSP10.0 | UHD Signage with Built-in MagicInfoS10, SSSP10.0 | UHD Signage with Built-in MagicInfoS10, SSSP10.0 | UHD Signage with Built-in MagicInfoS10, SSSP10.0 | UHD Signage with Built-in MagicInfoS10, SSSP10.0 | UHD Signage with Built-in MagicInfoS10, SSSP10.0 | |
| | | Operating System | Tizen 7.0 | Tizen 7.0 | Tizen 7.0 | Tizen 7.0 | Tizen 7.0 | Tizen 7.0 |
| | Internal Player | Processor | CA531.3GHz Quad-Core | CA531.3GHz Quad-Core | CA531.3GHz Quad-Core | CA531.3GHz Quad-Core | CA531.3GHz Quad-Core | CA531.3GHz Quad-Core |
| | | Storage (FDM) | 8GB (3GB available) | 8GB (3GB available) | 8GB (3GB available) | 8GB (3GB available) | 8GB (3GB available) | 8GB (3GB available) |
| | H/W | 2nd Gen. B2B Design | 2nd Gen. B2B Design | 2nd Gen. B2B Design | 2nd Gen. B2B Design | 2nd Gen. B2B Design | 2nd Gen. B2B Design | 2nd Gen. B2B Design |
| | | Center IR | Center IR | Center IR | Center IR | Center IR | Center IR | Center IR |
| | Special | S/S/W | Signage New Home Workspace (Microsoft365/VMWare/RDP) Custom Home Auto Source Switching & Recovery Dicom Simulation Mode Director Mode Upgradable Web-Engine Tizen Enterprise Platform Video Conference Solution Smart Calibration (Basic) | Signage New Home Workspace (Microsoft365/VMWare/RDP) Custom Home Auto Source Switching & Recovery Dicom Simulation Mode Director Mode Upgradable Web-Engine Tizen Enterprise Platform Video Conference Solution Smart Calibration (Basic) | Signage New Home Workspace (Microsoft365/VMWare/RDP) Custom Home Auto Source Switching & Recovery Dicom Simulation Mode Director Mode Upgradable Web-Engine Tizen Enterprise Platform Video Conference Solution Smart Calibration (Basic) | Signage New Home Workspace (Microsoft365/VMWare/RDP) Custom Home Auto Source Switching & Recovery Dicom Simulation Mode Director Mode Upgradable Web-Engine Tizen Enterprise Platform Video Conference Solution Smart Calibration (Basic) | Signage New Home Workspace (Microsoft365/VMWare/RDP) Custom Home Auto Source Switching & Recovery Dicom Simulation Mode Director Mode Upgradable Web-Engine Tizen Enterprise Platform Video Conference Solution Smart Calibration (Basic) | Signage New Home Workspace (Microsoft365/VMWare/RDP) Custom Home Auto Source Switching & Recovery Dicom Simulation Mode Director Mode Upgradable Web-Engine Tizen Enterprise Platform Video Conference Solution Smart Calibration (Basic) |
| | | S/W | Signage New Home Workspace (Microsoft365/VMWare/RDP) Custom Home Auto Source Switching & Recovery Dicom Simulation Mode Director Mode Upgradable Web-Engine Tizen Enterprise Platform Video Conference Solution Smart Calibration (Basic) | Signage New Home Workspace (Microsoft365/VMWare/RDP) Custom Home Auto Source Switching & Recovery Dicom Simulation Mode Director Mode Upgradable Web-Engine Tizen Enterprise Platform Video Conference Solution Smart Calibration (Basic) | Signage New Home Workspace (Microsoft365/VMWare/RDP) Custom Home Auto Source Switching & Recovery Dicom Simulation Mode Director Mode Upgradable Web-Engine Tizen Enterprise Platform Video Conference Solution Smart Calibration (Basic) | Signage New Home Workspace (Microsoft365/VMWare/RDP) Custom Home Auto Source Switching & Recovery Dicom Simulation Mode Director Mode Upgradable Web-Engine Tizen Enterprise Platform Video Conference Solution Smart Calibration (Basic) | Signage New Home Workspace (Microsoft365/VMWare/RDP) Custom Home Auto Source Switching & Recovery Dicom Simulation Mode Director Mode Upgradable Web-Engine Tizen Enterprise Platform Video Conference Solution Smart Calibration (Basic) | Signage New Home Workspace (Microsoft365/VMWare/RDP) Custom Home Auto Source Switching & Recovery Dicom Simulation Mode Director Mode Upgradable Web-Engine Tizen Enterprise Platform Video Conference Solution Smart Calibration (Basic) |
| Certification | Safety | 60950-1/62368-1 | 60950-1/62368-1 | 60950-1/62368-1 | 60950-1/62368-1 | 60950-1/62368-1 | 60950-1/62368-1 | |
| | EMC | Class B | Class B | Class B | Class B | Class B | Class A | |
| | Environment | ENERGY STAR 8.0, EPEAT | ENERGY STAR 8.0, EPEAT | ENERGY STAR 8.0, EPEAT | ENERGY STAR 8.0, EPEAT | ENERGY STAR 8.0, EPEAT | ENERGY STAR 8.0, EPEAT | |
| | IP Rating | IP5x | IP5x | IP5x | IP5x | IP5x | IP5x | |
| Power | Power Consumption | Max[W/h] | TBD | TBD | TBD | TBD | TBD | |
| | | Typical[W/h] | TBD | TBD | TBD | TBD | TBD | |
| Operating Condition | Temperature | less than 0.5W | less than 0.5W | less than 0.5W | less than 0.5W | less than 0.5W | less than 0.5W | |
| | Relative Humidity | 0°C~ 40°C | 0°C~ 40°C | 0°C~ 40°C | 0°C~ 40°C | 0°C~ 40°C | 0°C~ 40°C | |
| Accessories | Included | Quick Setup Guide, Warranty Card, Power Cord | Quick Setup Guide, Warranty Card, Power Cord | Quick Setup Guide, Warranty Card, Power Cord | Quick Setup Guide, Warranty Card, Power Cord | Quick Setup Guide, Warranty Card, Power Cord | Quick Setup Guide, Warranty Card, Power Cord | |
| | | Remote Controller & Batteries | Remote Controller & Batteries | Remote Controller & Batteries | Remote Controller & Batteries | Remote Controller & Batteries | Remote Controller & Batteries | |
| | Optional | Stand | WMN-L4355C | WMN-L4355C | WMN-L4355C | WMN-L4355C | WMN-L4355C | |
| Specialty | Mount | WMN-B505C | WMN-B505C | WMN-B505C | WMN-B505C | WMN-B505C | N/A | |
| | | TBD | TBD | TBD | TBD | TBD | TBD | |

* This specification is not a finalized version, so some specifications may change at the end of June.

About Samsung Electronics Co., Ltd.

Samsung Electronics Co., Ltd. inspires the world and shapes the future with transformative ideas and technologies. The company is redefining the worlds of TVs, smartphones, wearable devices, tablets, digital appliances, medical equipment, network systems, and semiconductor and LED solutions. For the latest news, please visit the Samsung Newsroom at news.samsung.com.

Smart Signage

For more information about Samsung Smart Signage, visit www.samsung.com/business

Copyright © 2023 Samsung Electronics Co. Ltd. All rights reserved. Samsung is a registered trademark of Samsung Electronics Co. Ltd. Specifications and designs are subject to change without notice. Non-metric weights and measurements are approximate. All data were deemed correct at time of creation. Samsung is not liable for errors or omissions. All brand, product, service names and logos are trademarks and/or registered trademarks of their respective owners and are hereby recognized and acknowledged.

Samsung Electronics Co., Ltd.

416, Maetan 3-dong, Yeongtong-gu, Suwon-si, Gyeonggi-do 443-772, Korea

2023-06



Crystal UHD Signage

QBC series

Slim design. Stunning performance.

Introducing the QBC series, the slimmest display in the Samsung's UHD signage offerings. This products deliver an unparalleled slim design that fits into any business, while delivering the visual quality to make a big impact. The sleek form factor is easily installed to fit any room design and delivers stunning visual performance. Dynamic Crystal Color and Quantum Processor Lite 4K delivering consistent, lifelike colors to any content. This is not just a display for simple advertising. It's a display that brings the solutions, tools, and picture quality to grow to your business, no matter what industry you're in.

Key features



Ultra Slim Depth

The unparalleled ultra-slim thickness of 28.5mm makes it the thinnest option in Samsung's UHD Signage series. It comes with the Slim Fit Wall Mount, which allows you to install it neatly and easily in any environment.



Even Bezels and Centered VESA Holes

The bezels are even on all four sides of the display for a consistent look, while the central VESA mounting holes ensure secure mounting and easy adjustability to portrait mode.



Dynamic Crystal Color

One billion shades of color let you see every subtlety with lifelike color variations. Images are clear and consistent thanks to Samsung's industry leading video processing and upscaling technology.



Smart Calibration

Guarantee complete brand consistency across every location. Using the Samsung mobile app, calibrate displays to showcase brand logos and other collateral in the exact colors required.



Energy star / EPEAT Bronze

Samsung is making diverse efforts to reduce our environmental impact in smart signage, and encouraging users to pursue a more sustainable life.