

Specifications

SAMSUNG

Model		QM43C	QM50C	QM55C	QM65C	QM75C	QM85C	
Display Panel	Diagonal Size	43	50	55	65	75	85	
	Class Measured	42.5	48.5	54.6	64.5	74.5	84.5	
	Resolution	3,840 x 2,160 (16:9)	3,840 x 2,160 (16:9)	3,840 x 2,160 (16:9)	3,840 x 2,160 (16:9)	3,840 x 2,160 (16:9)	3,840 x 2,160 (16:9)	
	Brightness (Typ.)	500 nit	500 nit	500 nit	500 nit	500 nit	500 nit	
	Orientation	Landscape/Portrait	Landscape/Portrait	Landscape/Portrait	Landscape/Portrait	Landscape/Portrait	Landscape/Portrait	
	Haze	25%	25%	25%	25%	25%	25%	
	Contrast Ratio (Typ.)	4,000:1 (* IPS - 1,200:1)	4,000:1 (* IPS - 1,200:1)	4,000:1	4,000:1	4,000:1	4,000:1	
	Type	VA/IPS	VA/IPS	VA	VA	VA	VA	
	Active Display Area	941.184 (H) x 529.416 (V)	1,095.84 (H) x 616.4 (V)	1,209.6 (H) x 680.4 (V)	1,428.48 (H) x 803.5 2(V)	1,650.24 (H) x 928.26 (V)	1,872.0 (H) x 1,053.01 (V)	
	Pixel Pitch (mm)	0.245 x 0.245	0.285 x 0.285	0.315 x 0.315	0.372 x 0.372	0.429 x 0.429	0.487 x 0.487	
Color Gamut	NTSC 72%	NTSC 72%	NTSC 72%	NTSC 72%	NTSC 72%	NTSC 72%		
Operation Hour	24/7	24/7	24/7	24/7	24/7	24/7		
Connectivity / Sound	Input	Video	DP1.2 (1), HDMI 2.0 (3)	DP1.2 (1), HDMI 2.0 (3)	DP1.2 (1), HDMI 2.0 (3)	DP1.2 (1), HDMI 2.0 (3)	DP1.2 (1), HDMI 2.0 (3)	
		Audio	N/A	N/A	N/A	N/A	N/A	
		USB	USB 2.0 x 2	USB 2.0 x 2	USB 2.0 x 2	USB 2.0 x 2	USB 2.0 x 2	
		Tuner	N/A	N/A	N/A	N/A	N/A	
		Video	N/A	N/A	N/A	N/A	N/A	
	Output	Audio	Stereo mini Jack	Stereo mini Jack	Stereo mini Jack	Stereo mini Jack	Stereo mini Jack	
		USB	N/A	N/A	N/A	N/A	N/A	
		WiFi / BT	O/O	O/O	O/O	O/O	O/O	
		External Control	RS232C (In/Out), RJ45	RS232C (In/Out), RJ45	RS232C (In/Out), RJ45	RS232C (In/Out), RJ45	RS232C (In/Out), RJ45	
		Speaker	10W 2ch	10W 2ch	10W 2ch	10W 2ch	10W 2ch	
Mechanical Spec	Dimension (mm)	Set	969.5 x 557.8 x 28.5	1,124.1 x 644.8 x 28.5	1,237.9 x 708.8 x 28.5	1,456.8 x 831.9 x 28.5	1,682.3 x 960.4 x 28.5	1,904.3 x 1,085.3 x 28.5
		Package	TBD	TBD	TBD	TBD	TBD	
	Weight (kg)	Set	TBD	TBD	TBD	TBD	TBD	
		Package	TBD	TBD	TBD	TBD	TBD	
	VESA Mount	200 x 200	200 x 200	200 x 200	400 x 300	400 x 400	400 x 400	
	VESA Mount Screw (Min-Max)	M8, 12-14mm	M8, 12-14mm	M8, 12-14mm	M8, 12-14mm	M8, 12-14mm		
Bezel Width (mm)	11.5 (Even)	11.5 (Even)	11.5 (Even)	11.5 (Even)	13.4 (Even)	13.9 (Even)		
Features	Key	UHD Signage with Built-in MagicInfoS10, SSSP 10.0	UHD Signage with Built-in MagicInfoS10, SSSP 10.0	UHD Signage with Built-in MagicInfoS10, SSSP 10.0	UHD Signage with Built-in MagicInfoS10, SSSP 10.0	UHD Signage with Built-in MagicInfoS10, SSSP 10.0	UHD Signage with Built-in MagicInfoS10, SSSP 10.0	
		Operating System	Tizen 7.0	Tizen 7.0	Tizen 7.0	Tizen 7.0	Tizen 7.0	
	Internal Player	Processor	CA731.6GHz Quad-Core	CA731.6GHz Quad-Core	CA731.6GHz Quad-Core	CA731.6GHz Quad-Core	CA731.6GHz Quad-Core	
		Storage (FDM)	16GB (10GB available)	16GB (10GB available)	16GB (10GB available)	16GB (10GB available)	16GB (10GB available)	
	Special	H/W	2nd Gen. B2B Design Center IR	2nd Gen. B2B Design Center IR	2nd Gen. B2B Design Center IR	2nd Gen. B2B Design Center IR	2nd Gen. B2B Design Center IR	
			Temperature Sensor	Temperature Sensor	Temperature Sensor	Temperature Sensor	Temperature Sensor	
			Ambient Sensor	Ambient Sensor	Ambient Sensor	Ambient Sensor	Ambient Sensor	
		S/W	Auto Level	Auto Level	Auto Level	Auto Level	Auto Level	
			Wi-Fi (2.4/5.0GHz dual) & BT	Wi-Fi (2.4/5.0GHz dual) & BT	Wi-Fi (2.4/5.0GHz dual) & BT	Wi-Fi (2.4/5.0GHz dual) & BT	Wi-Fi (2.4/5.0GHz dual) & BT	
			Signage New Home Workspace	Signage New Home Workspace	Signage New Home Workspace	Signage New Home Workspace	Signage New Home Workspace	
Microsoft 371/VMWare/RDP	Microsoft 371/VMWare/RDP	Microsoft 371/VMWare/RDP	Microsoft 371/VMWare/RDP	Microsoft 371/VMWare/RDP				
Custom Home	Custom Home	Custom Home	Custom Home	Custom Home				
Auto Source	Auto Source	Auto Source	Auto Source	Auto Source				
Switching & Recovery	Switching & Recovery	Switching & Recovery	Switching & Recovery	Switching & Recovery				
Dicom Simulation Mode	Dicom Simulation Mode	Dicom Simulation Mode	Dicom Simulation Mode	Dicom Simulation Mode				
Director Mode	Director Mode	Director Mode	Director Mode	Director Mode				
SmartView+	SmartView+	SmartView+	SmartView+	SmartView+				
Upgradable Web-Engine	Upgradable Web-Engine	Upgradable Web-Engine	Upgradable Web-Engine	Upgradable Web-Engine				
Tizen Enterprise Platform	Tizen Enterprise Platform	Tizen Enterprise Platform	Tizen Enterprise Platform	Tizen Enterprise Platform				
Video Conference Solution	Video Conference Solution	Video Conference Solution	Video Conference Solution	Video Conference Solution				
Smart Calibration	Smart Calibration	Smart Calibration	Smart Calibration	Smart Calibration				
Certification	Safety	60950-1/62368-1	60950-1/62368-1	60950-1/62368-1	60950-1/62368-1	60950-1/62368-1	60950-1/62368-1	
	EMC	Class B	Class B	Class B	Class B	Class B	Class A	
	Environment	ENERGY STAR 8.0, EPEAT	ENERGY STAR 8.0, EPEAT	ENERGY STAR 8.0, EPEAT	ENERGY STAR 8.0, EPEAT	ENERGY STAR 8.0, EPEAT		
	IP Rating	IP5x	IP5x	IP5x	IP5x	IP5x		
	Security	802.1x (WPA2 Enterprise) : EAP-TLS, EAP-TTLS, EAP-PEAP	802.1x (WPA2 Enterprise) : EAP-TLS, EAP-TTLS, EAP-PEAP	802.1x (WPA2 Enterprise) : EAP-TLS, EAP-TTLS, EAP-PEAP	802.1x (WPA2 Enterprise) : EAP-TLS, EAP-TTLS, EAP-PEAP	802.1x (WPA2 Enterprise) : EAP-TLS, EAP-TTLS, EAP-PEAP		
Power	Power Supply	AC100 - 240 V, 50/60 Hz	AC100 - 240 V, 50/60 Hz	AC100 - 240 V, 50/60 Hz	AC100 - 240 V, 50/60 Hz	AC100 - 240 V, 50/60 Hz	AC100 - 240 V, 50/60 Hz	
	Power Consumption	Max[W/h]	TBD	TBD	TBD	TBD	TBD	
		Typical[W/h]	TBD	TBD	TBD	TBD	TBD	
Operating Condition	Sleep mode	less than 0.5W	less than 0.5W	less than 0.5W	less than 0.5W	less than 0.5W		
	Temperature	0°C - 40°C	0°C - 40°C	0°C - 40°C	0°C - 40°C	0°C - 40°C		
Accessories	Included	Quick Setup Guide, Warranty Card, Power Cord	Quick Setup Guide, Warranty Card, Power Cord	Quick Setup Guide, Warranty Card, Power Cord	Quick Setup Guide, Warranty Card, Power Cord	Quick Setup Guide, Warranty Card, Power Cord		
		RS232C (In) Gender Remote Controller & Batteries	RS232C (In) Gender Remote Controller & Batteries	RS232C (In) Gender Remote Controller & Batteries	RS232C (In) Gender Remote Controller & Batteries	RS232C (In) Gender Remote Controller & Batteries		
	Optional	Stand	WMN-L4355C	WMN-L4355C	WMN-L4355C	WMN-L4355C	WMN-L4355C	
		Mount	WMN-B505C	WMN-B505C	WMN-B505C	WMN-B505C	N/A	
Specialty	TBD	TBD	TBD	TBD	TBD			

* This specification is not a finalized version, so some specifications may change at the end of June.

About Samsung Electronics Co., Ltd.

Samsung Electronics Co., Ltd. inspires the world and shapes the future with transformative ideas and technologies. The company is redefining the worlds of TVs, smartphones, wearable devices, tablets, digital appliances, medical equipment, network systems, and semiconductor and LED solutions. For the latest news, please visit the Samsung Newsroom at news.samsung.com.

Smart Signage

For more information about Samsung Smart Signage, visit www.samsung.com/business

Copyright © 2023 Samsung Electronics Co. Ltd. All rights reserved. Samsung is a registered trademark of Samsung Electronics Co. Ltd. Specifications and designs are subject to change without notice. Non-metric weights and measurements are approximate. All data were deemed correct at time of creation. Samsung is not liable for errors or omissions. All brand, product, service names and logos are trademarks and/or registered trademarks of their respective owners and are hereby recognized and acknowledged.

Samsung Electronics Co., Ltd.

416, Maetan 3-dong, Yeongtong-gu, Suwon-si, Gyeonggi-do 443-772, Korea

2023-06



Crystal UHD Signage

QMC series

Slim design. Stunning performance.

Introducing the QMC series, the slimmest display in the Samsung's UHD signage offerings. This products deliver an unparalleled slim design that fits into any business, while delivering the visual quality to make a big impact. The sleek form factor is easily installed to fit any room design and delivers stunning visual performance. Dynamic Crystal Color and Quantum Processor Lite 4K delivering consistent, lifelike colors to any content. This is not just a display for simple advertising. It's a display that brings the solutions, tools, and picture quality to grow to your business, no matter what industry you're in.

Key features



Ultra Slim Depth

The unparalleled ultra-slim thickness of 28.5mm makes it the thinnest option in Samsung's UHD Signage series. It comes with the Slim Fit Wall Mount, which allows you to install it neatly and easily in any environment.



Even Bezels and Centered VESA Holes

The bezels are even on all four sides of the display for a consistent look, while the central VESA mounting holes ensure secure mounting and easy adjustability to portrait mode.



Dynamic Crystal Color

One billion shades of color let you see every subtlety with lifelike color variations. Images are clear and consistent thanks to Samsung's industry leading video processing and upscaling technology.



Smartview+

In the QMC series, SmartView+ enables wireless screen sharing for easy collaboration and quick screen switching with just a click.



Smart Calibration

Guarantee complete brand consistency across every location. Using the Samsung mobile app, calibrate displays to showcase brand logos and other collateral in the exact colors required.



Energy star / EPEAT Bronze / TÜV Rheinland Carbon Footprint

Samsung is making diverse efforts to reduce our environmental impact in smart signage, and encouraging users to pursue a more sustainable life.